


# Al- Pressverbinder mit Cu-Bolzen für zugentlastete Verbindungen


DIN

- für AL-Seile nach DIN 48201 Teil 1, Al-Seile nach DIN EN 50182
- Werkstoff: AL 99,5% DIN 40501, E-CU DIN 40500
- Oberfläche blank
- Pressmarkierung • inkl. Kontaktfett



Al  
Cu

- zum Verschrauben von Al-Verbindungen an Cu-Klemmen

Art. Nr.	LQ rm/sm	se	d1	d4	GL	I	ØBo.	ØSe.	KZ Al	kg/100		VE
293960	<b>25</b>	35	6,8	12,0	58	20,0	6	6,3	12	1,600		1
293962	<b>35</b>	35	8,0	14,0	71	22,0	7	7,5	14	2,800		1
293964	<b>50</b>	50	10,0	16,0	74	25,0	8	9,0	16	3,800		1
293966	<b>70</b>	70	11,5	18,5	87	30,0	10	10,0	18	5,400		1
293968	<b>95</b>	120	13,2	23,0	91	33,0	12	12,5	22	10,600		1
293970	<b>120</b>	150	15,0	23,0	97	38,0	12	14,0	22	9,000		1
293972	<b>150</b>	185	16,5	25,5	108	38,0	12	15,8	25	10,900		1
293974	<b>185</b>	240	18,5	28,5	116	44,0	14	17,5	28	15,700		1
293976	<b>240</b>	300	21,5	32,5	128	44,0	16	20,3	32	17,000		1
293978	<b>300</b>	-	23,5	34,5	131	46,0	18	22,5	34	23,200		1