



Coupling for FFVYN

Product description:

The PVC coupling for FFVYN is non-flame propagating and available in black (RAL9005).

This coupling is used for the connection of FFVYN.

Art-No.:	Type	Overall-length mm
18550050	50	95,0
18550065	65	95,0
18550080	80	95,0
18550100	100	100,0
18550125	125	120,0
18550160	160	160,0
18550200	200	160,0

*Available upon request

All dimensions without tolerances are only for information

Material properties		
Zero halogen	DIN VDE V 0604-2-100	
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	●
UV-resistant	DIN 53387	
Highspeed		

Scope			
on plaster		machines	
under plaster		hot asphalt	
on wood		under screed	
underground installation		prefabricated construction	
in concrete		outdoor	

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, nitric acid, hydrochloric acid, sulfuric acid, terpentine, detergent
Limitedly resistant to	gaseous dry chlorine
Not resistant to	benzene, beer

Hotline	
<p>Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time. If you generously install a system of unused conduits today, you can easily expand your electrical installations later. You save lots of time, money and effort!</p>	<p>We are happy to help you with any technical questions. Prompt information can be obtained from our technical consultants at +49 9525 88-8123</p>