



RMKu-E-H0

Product description:



RMKu-E-H0 is a plastic push-fit coupling made of special plastic, in black (RAL 9005), non-flame propagating, zero halogen.

This coupling is used for all zero halogen corrugated conduits. An advantage is that it does not contain halogens which prevents the generation of dangerous toxic and corrosive gases.



VDE 0605
DIN EN 61386-22
zero halogen acc. to DIN EN 50267-2-2

Art-No.:	Type	Outside Ø mm	Content	PU	Weight PU/kg	Overall-length mm
25910016	16	17,3	25	STK	0,025	56,0
25910020	20	21,6	50	STK	0,150	56,0
25910025	25	26,7	50	STK	0,250	75,0
25910032	32	33,7	25	STK	0,150	75,0
25910040	40	41,8	25	STK	0,300	102,0
25910050	50	51,5	10	STK	0,170	102,0

All dimensions without tolerances are only for information

Material properties		
Zero halogen	DIN VDE V 0604-2-100	●
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	●
UV-resistant	DIN 53387	
Highspeed		

Scope			
on plaster	●	machines	●
under plaster	●	hot asphalt	
on wood	●	under screed	●
underground installation		prefabricated construction	●
in concrete	●	outdoor	

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, beer, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, hydrochloric acid, sulfuric acid, detergent
Limitedly resistant to	gasoline, benzene, nitric acid
Not resistant to	gaseous dry chlorine, terpentine



RMKu-E-H0

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time. If you generously install a system of unused conduits today, you can easily expand your electrical installations later. You save lots of time, money and effort!

We are happy to help you with any technical questions. Prompt information can be obtained from our technical consultants at +49 9525 88-8123